

GSA - GMA

RIT PP - PNEUMATIC

Load capacity up to 70kg







RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

RIT PP - Pneumatic - Nylon Wheel Center. (-20°C to + 50°C)
 Manufactured with tire and tube and nylon injected wheel center. Indicated for applications in irregular floors where handling easiness, and impact and vibration damping is required. They offer easy maintenance, and their components can be supplied separately. Nominal working speed is up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)			
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)
GSA 2504 PPN	FSA 2504 PPN	GMA 2504 PPN	FMA 2504 PPN	RIT 2504 PPN				Nylon Socket			
GSA 2504 PPR	FSA 2504 PPR	GMA 2504 PPR	FMA 2504 PPR	RIT 2504 PPR	215	60	1/2"	Roller Bearing	70	256	165
GSA 2504 PPE	FSA 2504 PPE	GMA 2504 PPE	FMA 2504 PPE	RIT 2504 PPE				Ball Bearing			

Fittings/Accessories



Axle hole
13mm



Threaded Stem
1/2"NC X 30mm




Threaded Stem
1/2"NC X 70mm





Long stem

Reference	SAES	SAE	SAEX	See table below
-----------	------	-----	------	-----------------

Swivel Sections





Top Plate Options



Brake Options



FL - Side Brake

RUBBER EXPANDER FITTING 		ALUMINUM EXPANDER FITTING 		LONG STEM FITTING		
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	CODE	Ø	HEIGHT
18 - 21	EX 1			SAEL 1	1"	150mm
21 - 24	EX 2	21 - 27	EA 2	SAEL 2	1.1/4"	
25 - 28	EX 3	27 - 33	EA 4	SAEL 3	1.5/16"	
27 - 30	EX 4					
37 - 40	EX 5					