

# Dolly Extra Axial - DE/DERX

## P - MOLDED POLYURETHANE







Load capacity up to 6000kg

**RIG** Reinforced rig, made of carbon steel, swivel section with axial ball bearing and taper roller bearings. Painted finishing. Bolted wheel axle.



### WHEEL

P - Molded Polyurethane. Hardness: 90 Shore A. (-40°C to + 80°C)  
Produced with a molded polyurethane tread and grey cast iron wheel center. Ideal for applications on various surface and environment types. They withstand high loads, protect the floor, require less effort to handle, produce low noise level during handling, and have an excellent service life. They have great resistance to abrasion, impacts, weathering and chemicals such as greases, oils, salts and solvents. They can be used at a speed of up to 20km/h when mounted with ball bearings.

Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)			
Reference	Reference	Reference	(mm)	(mm)	(mm)		KG	(mm)	(mm)
GDE 123 PE	FDE 123 PE	R 123 PE	300	151	30	Ball Bearing	2600	410	230
GDE 124 PE	FDE 124 PE	R 124 PE		213			4000		
GDE 165 PE	FDE 165 PE	R 165 PE	400	193	35		5600	540	300
GDE 205 PE	FDE 205 PE	R 205 PE	500	248	40		6000	600	350

### Accessories/Brake Options




FL - Side Brake




BG - Swivel Lock

### Swivel Sections


### Top Plate Options




GDE



GDE / GDERX



FDE 123 / 124



FDE 165 / 205