

# GSA - GMA

## BP - PVC

Load capacity up to 300kg

**RIG** Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



### WHEEL

BP - Thermoplastic Compound with PVC. Hardness: 80 Shore A. (-10°C to +50°C)  
Produced with recyclable thermoplastic compound with PVC tread and polypropylene copolymer wheel center. They offer a soft and quiet rolling, great floor protection, good chemical, wear and impact resistance, resulting in an excellent cost-benefit ratio. Nominal working speed is up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)	KG			
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)			(mm)	w/o brake (mm)	w/ brake FP (mm)
GSA 52 BPN	FSA 52 BPN	GMA 52 BPN	FMA 52 BPN	R 52 BPN	125	50	1/2"	Nylon Socket	200	165	110	110
GSA 52 BPR	FSA 52 BPR	GMA 52 BPR	FMA 52 BPR	R 52 BPR								
GSA 52 BPE	FSA 52 BPE	GMA 52 BPE	FMA 52 BPE	R 52 BPE								
GSA 62 BPN	FSA 62 BPN	GMA 62 BPN	FMA 62 BPN	R 62 BPN	150	50	1/2"	Nylon Socket	250	196	122	128
GSA 62 BPR	FSA 62 BPR	GMA 62 BPR	FMA 62 BPR	R 62 BPR								
GSA 62 BPE	FSA 62 BPE	GMA 62 BPE	FMA 62 BPE	R 62 BPE								
GSA 82 BPN	FSA 82 BPN	GMA 82 BPN	FMA 82 BPN	R 82 BPN	200	50	1/2"	Nylon Socket	300	240	158	158
GSA 82 BPE	FSA 82 BPE	GMA 82 BPE	FMA 82 BPE	R 82 BPE								

### Fittings/Accessories



Axle hole  
13mm



Threaded Stem  
1/2"NC X 30mm



Threaded Stem  
1/2"NC X 70mm



Long stem

Reference


SAES

SAE



SAEX

See table below

### Swivel Sections



### Top Plate Options



### Brake Options



FP - Pedal Brake



FL - Side Brake

RUBBER EXPANDER FITTING		ALUMINUM EXPANDER FITTING		LONG STEM FITTING		
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	CODE	Ø	HEIGHT
18 - 21	EX 1	21 - 27	EA 2	SAEL 1	1"	150mm
21 - 24	EX 2			SAEL 2	1.1/4"	
25 - 28	EX 3	27 - 33	EA 4	SAEL 3	1.5/16"	
27 - 30	EX 4					
37 - 40	EX 5					