

GSA - GMA

TP - THERMOPLASTIC COMPOUND

Load capacity up to 300kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

TP - Thermoplastic Compound. Hardness: 80 Shore A. (-10°C to +50°C)
Produced with recyclable thermoplastic compound tread and polypropylene copolymer wheel center. They offer a soft and quiet rolling, excellent floor protection, good chemical, wear and impact resistance, resulting in an excellent cost-benefit ratio. Nominal working speed is up to 4km/h.



| Swivel Caster | Rigid Caster | Swivel Caster | Rigid Caster | Wheel | (mm) | (mm) | (pol) | Axle Type (bearing) | KG | (mm) | w/o brake (mm) | w/ brake FP (mm) |
|---------------|--------------|---------------|--------------|----------------|------|------|-------|---------------------|-----|------|----------------|------------------|
| Reference | Reference | Reference | Reference | Reference | | | | | | | | |
| GSA 52 TPN | FSA 52 TPN | GMA 52 TPN | FMA 52 TPN | R 52 TPN | 125 | 50 | 1/2" | Nylon Socket | 200 | 165 | 110 | 110 |
| GSA 52 TPR | FSA 52 TPR | GMA 52 TPR | FMA 52 TPR | Roller Bearing | | | | | | | | |
| GSA 52 TPE | FSA 52 TPE | GMA 52 TPE | FMA 52 TPE | Ball Bearing | | | | | | | | |
| GSA 62 TPN | FSA 62 TPN | GMA 62 TPN | FMA 62 TPN | R 62 TPN | 150 | 50 | 1/2" | Nylon Socket | 250 | 196 | 122 | 128 |
| GSA 62 TPR | FSA 62 TPR | GMA 62 TPR | FMA 62 TPR | Roller Bearing | | | | | | | | |
| GSA 62 TPE | FSA 62 TPE | GMA 62 TPE | FMA 62 TPE | Ball Bearing | | | | | | | | |
| GSA 82 TPN | FSA 82 TPN | GMA 82 TPN | FMA 82 TPN | R 82 TPN | 200 | 50 | 1/2" | Nylon Socket | 300 | 240 | 158 | 158 |
| GSA 82 TPE | FSA 82 TPE | GMA 82 TPE | FMA 82 TPE | Ball Bearing | | | | | | | | |

Fittings/Accessories



Axle hole
13mm



Threaded Stem
1/2"NC X 30mm



Threaded Stem
1/2"NC X 70mm






Long stem

| | | | | |
|-----------|------|-----|------|-----------------|
| Reference | SAES | SAE | SAEX | See table below |
|-----------|------|-----|------|-----------------|

Swivel Sections

Top Plate Options

Brake Options



FP - Pedal Brake



FL - Side Brake

| RUBBER EXPANDER FITTING | | ALUMINUM EXPANDER FITTING | | LONG STEM FITTING | | |
|-------------------------|-----------|---------------------------|-----------|-------------------|---------|--------|
| SIZE (mm) | REFERENCE | SIZE (mm) | REFERENCE | CODE | Ø | HEIGHT |
| 18 - 21 | EX 1 | 21 - 27 | EA 2 | SAEL 1 | 1" | 150mm |
| 21 - 24 | EX 2 | | | SAEL 2 | 1.1/4" | |
| 25 - 28 | EX 3 | 27 - 33 | EA 4 | SAEL 3 | 1.5/16" | |
| 27 - 30 | EX 4 | | | | | |
| 37 - 40 | EX 5 | | | | | |