

GSA - GMA

STR - THERMOPLASTIC RUBBER

Load capacity up to 250kg








RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

STR - Thermoplastic Rubber. Hardness: 70 Shore A. (-20°C to +70°C)
Produced with recyclable thermoplastic rubber tread and polypropylene copolymer center. Wheel tread profile has a grooved pattern enabling a better adherence in external and internal floors. They offer a soft and quiet rolling, excellent floor protection, good chemical resistance, and wear and impact resistance. Nominal working speed is up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GSA 62 STR	FSA 62 STR	GMA 62 STR	FMA 62 STR	R 62 STR	150	50	1/2"	Ball Bearing	250	196	122	128

Fittings/Accessories



Axle hole
13mm

Reference

SAES



Threaded Stem
1/2"NC X 30mm

SAE



Threaded Stem
1/2"NC X 70mm


SAEX





Long stem

See table below

Swivel Sections



Top Plate Options





Brake Options



FP - Pedal Brake



FL - Side Brake

RUBBER EXPANDER FITTING 		ALUMINUM EXPANDER FITTING 		LONG STEM FITTING		
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	CODE	Ø	HEIGHT
18 - 21	EX 1	21 - 27	EA 2	SAEL 1	1"	150mm
21 - 24	EX 2			SAEL 2	1.1/4"	
25 - 28	EX 3	27 - 33	EA 4	SAEL 3	1.5/16"	
27 - 30	EX 4					
37 - 40	EX 5					