

GSA - GMA

AC - MOLDED POLYURETHANE

Load capacity up to 550kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

AC - Molded High Hardness Polyurethane - Round. Hardness: 60 Shore D. (-40°C to + 80°C)
Produced with a high hardness molded green polyurethane tread over a grey cast iron wheel center. Round tread profile offers a reduced floor contact area, easiness for handling and maneuvering, reducing handling effort and low rolling noise level. They offer a superior service life due to their polyurethane layer larger than conventional wheels. They have an excellent resistance to abrasion, impacts, weathering and chemicals such as greases, oils, salts and solvents. Nominal working speed is up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel	(mm)	(mm)	(pol)	Axle Type (bearing)	KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GSA 52 ACE	FSA 52 ACE	GMA 52 ACE	FMA 52 ACE	R 52 ACE	125				350	165	110	110
GSA 62 ACE	FSA 62 ACE	GMA 62 ACE	FMA 62 ACE	R 62 ACE	150	50	1/2"	Ball Bearing	400	196	122	128
GSA 82 ACE	FSA 82 ACE	GMA 82 ACE	FMA 82 ACE	R 82 ACE	200				550	240	158	158

Fittings/Accessories



Axle hole
13mm



Threaded Stem
1/2"NC X 30mm



Threaded Stem
1/2"NC X 70mm






Long stem

Reference	SAES	SAE	SAEX	See table below
-----------	------	-----	------	-----------------

Swivel Sections

Top Plate Options

Brake Options



FP - Pedal Brake



FL - Side Brake

RUBBER EXPANDER FITTING	
SIZE (mm)	REFERENCE
18 - 21	EX 1
21 - 24	EX 2
25 - 28	EX 3
27 - 30	EX 4
37 - 40	EX 5

ALUMINUM EXPANDER FITTING	
SIZE (mm)	REFERENCE
21 - 27	EA 2
27 - 33	EA 4

LONG STEM FITTING		
CODE	Ø	HEIGHT
SAEL 1	1"	150mm
SAEL 2	1.1/4"	
SAEL 3	1.5/16"	