

GSA - GMA

B - MOLDED RUBBER

Load capacity up to 350kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

B - Molded Rubber. Hardness: 80 Shore A. (-20°C to + 70°C)
Produced with molded vulcanized rubber tread over a grey cast iron wheel center. They roll softly with a low noise level, absorb shocks and vibrations. They are resistant to abrasion and chemicals. They can be used at a speed of up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GSA 52 BN	FSA 52 BN	GMA 52 BN	FMA 52 BN	R 52 BN	125	50	1/2"	Nylon Socket	250	165	110	110
GSA 52 BR	FSA 52 BR	GMA 52 BR	FMA 52 BR	R 52 BR				Roller Bearing				
GSA 52 BE	FSA 52 BE	GMA 52 BE	FMA 52 BE	R 52 BE				Ball Bearing				
GSA 62 BN	FSA 62 BN	GMA 62 BN	FMA 62 BN	R 62 BN	150	50	1/2"	Nylon Socket	300	196	122	128
GSA 62 BR	FSA 62 BR	GMA 62 BR	FMA 62 BR	R 62 BR				Roller Bearing				
GSA 62 BE	FSA 62 BE	GMA 62 BE	FMA 62 BE	R 62 BE				Ball Bearing				
GSA 82 BN	FSA 82 BN	GMA 82 BN	FMA 82 BN	R 82 BN	200	50	1/2"	Nylon Socket	350	240	158	158
GSA 82 BR	FSA 82 BR	GMA 82 BR	FMA 82 BR	R 82 BR				Roller Bearing				
GSA 82 BE	FSA 82 BE	GMA 82 BE	FMA 82 BE	R 82 BE				Ball Bearing				

Fittings/Accessories



Axle hole
13mm



Threaded Stem
1/2"NC X 30mm



Threaded Stem
1/2"NC X 70mm



Long stem

Reference


SAES

SAE



SAEX

See table below

Swivel Sections



Top Plate Options



Brake Options



FP - Pedal Brake



FL - Side Brake

RUBBER EXPANDER FITTING		ALUMINUM EXPANDER FITTING		LONG STEM FITTING		
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	CODE	Ø	HEIGHT
18 - 21	EX 1	21 - 27	EA 2	SAEL 1	1"	150mm
21 - 24	EX 2			SAEL 2	1.1/4"	
25 - 28	EX 3	27 - 33	EA 4	SAEL 3	1.5/16"	
27 - 30	EX 4					
37 - 40	EX 5					