

# GSA - GMA

## RIT - PNEUMATIC

Load capacity up to 70kg









**RIG** Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.

### WHEEL

RIT - Pneumatic - Stamped Plate Wheel Center (-20°C to + 50°C)  
Manufactured with tire and tube, with zinc-plated stamped carbon steel plates. Indicated for applications in irregular floors where handling easiness, impact and vibration damping is required. They offer an easy maintenance, and their components can be supplied separately. Nominal working speed is up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)			
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)
GSA 2504 N	FSA 2504 N	GMA 2504 N	FMA 2504 N	RIT 2504 N				Nylon Socket			
GSA 2504 R	FSA 2504 R	GMA 2504 R	FMA 2504 R	RIT 2504 R	215	60	1/2"	Roller Bearing	70	256	165
GSA 2504 E	FSA 2504 E	GMA 2504 E	FMA 2504 E	RIT 2504 E				Ball Bearing			

### Fittings/Accessories



Axle hole  
13mm



Threaded Stem  
1/2"NC X 30mm




Threaded Stem  
1/2"NC X 70mm





Long stem

Reference	SAES	SAE	SAEX	See table below
-----------	------	-----	------	-----------------

### Swivel Sections





### Top Plate Options



### Brake Options



FL - Side Brake

RUBBER EXPANDER FITTING 		ALUMINUM EXPANDER FITTING 		LONG STEM FITTING		
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	CODE	Ø	HEIGHT
18 - 21	EX 1	21 - 27	EA 2	SAEL 1	1"	150mm
21 - 24	EX 2			SAEL 2	1.1/4"	
25 - 28	EX 3	27 - 33	EA 4	SAEL 3	1.5/16"	
27 - 30	EX 4					
37 - 40	EX 5					