

GS - GM

P - MOLDED POLYURETHANE

Load capacity up to 700kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

P - Molded Polyurethane. Hardness: 90 Shore A. (-40°C to +80°C)

Produced with a molded polyurethane tread and grey cast iron wheel center. Ideal for applications on various surface and environment types. They withstand high loads, protect the floor, require less effort to handle, produce low noise level during handling, and have an excellent service life. They have great resistance to abrasion, impacts, weathering and chemicals such as greases, oils, salts and solvents. They can be used at a speed of up to 4km/h.



Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)	KG				
Reference	Reference	Reference	Reference	Reference	(mm)	(mm)	(pol)			(mm)	w/o brake (mm)	w/ brake FP (mm)	w/ brake GB (mm)
GS 42 PN	FS 42 PN	GM 42 PN	FM 42 PN	R 42 PN	100	50	1/2"	Nylon Socket	500	138	87	150	-
GS 42 PR	FS 42 PR	GM 42 PR	FM 42 PR	R 42 PR				Roller Bearing					
GS 42 PE	FS 42 PE	GM 42 PE	FM 42 PE	R 42 PE	125	50	1/2"	Ball Bearing	600	165	100	167	180
GS 52 PN	FS 52 PN	GM 52 PN	FM 52 PN	R 52 PN				Nylon Socket					
GS 52 PR	FS 52 PR	GM 52 PR	FM 52 PR	R 52 PR	150	50	1/2"	Roller Bearing	700	196	121	183	185
GS 52 PE	FS 52 PE	GM 52 PE	FM 52 PE	R 52 PE				Ball Bearing					
GS 62 PN	FS 62 PN	GM 62 PN	FM 62 PN	R 62 PN	175	50	1/2"	Nylon Socket	700	222	140	197	-
GS 62 PR	FS 62 PR	GM 62 PR	FM 62 PR	R 62 PR				Roller Bearing					
GS 62 PE	FS 62 PE	GM 62 PE	FM 62 PE	R 62 PE	200	50	1/2"	Ball Bearing	700	235	153	210	-
GS 72 PN	FS 72 PN	GM 72 PN	FM 72 PN	R 72 PN				Nylon Socket					
GS 72 PR	FS 72 PR	GM 72 PR	FM 72 PR	R 72 PR	225	50	1/2"	Roller Bearing	700	280	180	222	-
GS 72 PE	FS 72 PE	GM 72 PE	FM 72 PE	R 72 PE				Ball Bearing					
GS 82 PN	FS 82 PN	GM 82 PN	FM 82 PN	R 82 PN	250	50	1/2"	Nylon Socket	700	292	193	235	-
GS 82 PR	FS 82 PR	GM 82 PR	FM 82 PR	R 82 PR				Roller Bearing					
GS 82 PE	FS 82 PE	GM 82 PE	FM 82 PE	R 82 PE	275	50	1/2"	Ball Bearing	700	330	220	270	-
GS 92 PN	FS 92 PN	GM 92 PN	FM 92 PN	R 92 PN				Nylon Socket					
GS 92 PR	FS 92 PR	GM 92 PR	FM 92 PR	R 92 PR	300	50	1/2"	Roller Bearing	700	360	250	300	-
GS 92 PE	FS 92 PE	GM 92 PE	FM 92 PE	R 92 PE				Ball Bearing					
GS 102 PN	FS 102 PN	GM 102 PN	FM 102 PN	R 102 PN	325	50	1/2"	Nylon Socket	700	390	280	330	-
GS 102 PR	FS 102 PR	GM 102 PR	FM 102 PR	R 102 PR				Roller Bearing					
GS 102 PE	FS 102 PE	GM 102 PE	FM 102 PE	R 102 PE	350	50	1/2"	Ball Bearing	700	420	310	360	-
GS 102 PN	FS 102 PN	GM 102 PN	FM 102 PN	R 102 PN				Nylon Socket					

Fittings/Accessories



Axle hole
13mm

Reference
SES



Threaded Stem
1/2"NC X 32mm

Reference
SE



Threaded Stem
1/2"NC X 64mm


Reference
SEX







Long stem

Reference
See table below

Swivel Sections



Top Plate Options



Brake Options



GB* - Pedal Brake



FP - Pedal Brake



FL - Side Brake

LONG STEM FITTING		
CODE	Ø	HEIGHT
ME 1	1"	150mm
ME 2	1.1/4"	
ME 3	1.5/16"	

*Available only for 52 and 62