

GS - GM

RIT - PNEUMATIC

Load capacity up to 100kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.










RIT 3504 R

WHEEL

RIT - Pneumatic - Stamped Plate Wheel Center (-20°C to + 50°C)
Manufactured with tire and tube, with zinc-plated stamped carbon steel plates. Indicated for applications in irregular floors where handling easiness, impact and vibration damping is required. They offer an easy maintenance, and their components can be supplied separately. Nominal working speed is up to 4km/h.



Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GS 2504 N	FS 2504 N	RIT 2504 N	215	60	1/2"	Nylon Socket	70	251	165	220
GS 2504 R	FS 2504 R	RIT 2504 R				Roller Bearing				
GS 2504 E	FS 2504 E	RIT 2504 E				Ball Bearing				
GS 3504 N	FS 3504 N	RIT 3504 N	270	80	1/2"	Nylon Socket	100	312	208	-
GS 3504 R	FS 3504 R	RIT 3504 R				Roller Bearing				
GS 3504 E	FS 3504 E	RIT 3504 E				Ball Bearing				
GS 3504 PPN	FS 3504 PPN	RIT 3504 PPN				Nylon Socket				
GS 3504 PPR	FS 3504 PPR	RIT 3504 PPR				Roller Bearing				
GS 3504 PPE	FS 3504 PPE	RIT 3504 PPE				Ball Bearing				

Fittings/Accessories



Axle hole
13mm



Threaded Stem
1/2"NC X 32mm



Threaded Stem
1/2"NC X 64mm








Long stem

Reference	SES	SE	SEX	See table below
-----------	-----	----	-----	-----------------

Swivel Sections

Top Plate Options



Brake Options



GB* - Pedal Brake



FL - Side Brake

LONG STEM FITTING		
CODE	Ø	HEIGHT
ME 1	1"	150mm
ME 2	1.1/4"	
ME 3	1.5/16"	

*Available only for 52 and 62