# MX - Axial Medium

## P-MOLDED POLYURETHANE

## Load capacity up to 900kg

RIG

Made of steel with a painted finish and swivel section with two axial ball bearings. Bolted wheel axle









WHEEL

P - Molded Polyurethane. Hardness: 90 Shore A. (-40°C to + 80°C)

Produced with a molded polyurethane tread and grey cast iron wheel center. Ideal for applications on various surface and environment types The withstand high loads, protect the floor, require less effort to handle, produce low noise level during handling, and have an excellent service life. They have great resistance to abrasion, impacts, weathering and chemicals such as greases, oils, salts and solvents. They can be used at a speed of up to 20km/h when mounted with ball bearings.

Swivel Caster	Rigid Caster	Wheel			(D)	Axle Type	KG				
Reference	Reference	Reference	(mm) (mm)	(mm)	(pol)	(bearing)	[ KO	(mm)	w/o brake (mm)	w/ brake FP (mm)	w/ brake GB (mm)
GMX 42 PR	FMX 42 PR	R 42 PR	100	50	1/2"	Ball Bearing	500	155	84	143	
GMX 42 PE	FMX 42 PE	R 42 PE				Roller Bearing					
GMX 52 PR	FMX 52 PR	R 52 PR	125			Ball Bearing	600	183	107	155	183
GMX 52 PE	FMX 52 PE	R 52 PE				Roller Bearing					
GMX 62 PR	FMX 62 PR	R 62 PR	150			Ball Bearing	700	205	123	170	200
GMX 62 PE	FMX 62 PE	R 62 PE				Roller Bearing					
GMX 72 PR	FMX 72 PR	R 72 PR	175			Ball Bearing	800	238	145	180	-
GMX 72 PE	FMX 72 PE	R 72 PE				Roller Bearing					
GMX 82 PR	FMX 82 PR	R 82 PR	200			Ball Bearing	900	251	158	193	-
GMX 82 PE	FMX 82 PE	R 82 PE				Roller Bearing					
GMX 92 PR	FMX 92 PR	R 92 PR	225			Ball Bearing		294	185	212	-
GMX 92 PE	FMX92 PE	R 92 PE				Roller Bearing					
GMX 102 PR	FMX 102 PR	R 102 PR	250			Ball Bearing		306	197	225	-
GMX 102 PE	FMX 102 PE	R 102 PE				Roller Bearing					

#### **Accessories**







FLD - Side Brake Duplo



GB - Pedal Brake



FP - Pedal Brake



AH - Central Brake Consult the swivel hight for this type of brake




BG - Swivel Lock



GC - Caster Guard

### **Swivel Sections**



#### **Top Plate Options**

