

ERGONOMIC

BC - MOLDED POLYURETHANE

Load capacity up to 800kg








RIG Reinforced without central pin, with single hardened and guarded ball raceway. Bolted wheel axle.



WHEEL

BC - Molded Polyurethane - Round. Hardness: 90 Shore A. (-40°C to + 80°C)
Produced with a molded polyurethane tread and grey cast iron wheel center. Round tread profile offers a reduced floor contact area, easiness for handling and maneuvering, reducing handling effort and low rolling noise level. They offer a superior service life due to their polyurethane layer larger than conventional wheels. They have an excellent resistance to abrasion, impacts, weathering and chemicals such as greases, oils, salts and solvents. They can be used at a speed of up to 20km/h when mounted with ball bearings.



Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GKSR 42 BCE	FKSR 42 BCE	R 42 BCE	100	50	1/2"	Ball Bearing	400	143	75	135
GKSR 52 BCE	FKSR 52 BCE	R52 BCE	125				450	165	92	140
GKSR 62 BCE	FKSR 62 BCE	R62 BCE	150				550	190	132	180
GKSR 82 BCE	FKSR 82 BCE	R82 BCE	200				650	241	173	210
GKSR 102 BCE	FKSR 102 BCE	R102 BCE	250				700	290	213	241
GKSR 122 BCE	FKSR 122 BCE	R122 BCE	300				800	343	254	-

Accessories/Brake Options



Side Brake - FL



Pedal Brake - FP




Swivel Lock - AD



Caster Guard - GC

Swivel Sections



Top Plate Options

