

# ERGONOMIC

## B - MOLDED RUBBER








Load capacity up to 450kg

**RIG** Reinforced without central pin, with single hardened and guarded ball raceway. Bolted wheel axle.



### WHEEL

B - Molded Rubber. Hardness: 80 Shore A. (-20°C to + 70°C)  
Produced with molded vulcanized rubber tread over a grey cast iron wheel center. They roll softly with a low noise level, absorb shocks and vibrations. They are resistant to abrasion and chemicals. They can be used at a speed of up to 20km/h when mounted with ball bearings.

Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GKSR 42 BN	FKSR 42 BN	R 42 BN	100	50	1/2"	Nylon Socket	200	143	75	135
GKSR 42 BR	FKSR 42 BR	R 42 BR				Roller Bearing				
GKSR 42 BE	FKSR 42 BE	R 42 BE				Ball Bearing				
GKSR 52 BN	FKSR 52 BN	R 52 BN	125			Nylon Socket	250	165	92	140
GKSR 52 BR	FKSR 52 BR	R 52 BR				Roller Bearing				
GKSR 52 BE	FKSR 52 BE	R 52 BE				Ball Bearing				
GKSR 62 BN	FKSR 62 BN	R 62 BN	150			Nylon Socket	300	190	132	180
GKSR 62 BR	FKSR 62 BR	R 62 BR				Roller Bearing				
GKSR 62 BE	FKSR 62 BE	R 62 BE				Ball Bearing				
GKSR 82 BN	FKSR 82 BN	R 82 BN	200			Nylon Socket	350	241	173	210
GKSR 82 BR	FKSR 82 BR	R 82 BR				Roller Bearing				
GKSR 82 BE	FKSR 82 BE	R 82 BE				Ball Bearing				
GKSR 102 BN	FKSR 102 BN	R 102 BN	250	Nylon Socket	450	290	211	240		
GKSR 102 BR	FKSR 102 BR	R 102 BR		Roller Bearing						
GKSR 102 BE	FKSR 102 BE	R 102 BE		Ball Bearing						

### Accessories/Brake Options



Side Brake - FL



Pedal Brake - FP




Swivel Lock - AD



Caster Guard - GC

### Swivel Sections



### Top Plate Options

