



ERGONOMIC F - CAST IRON








Load capacity up to 900kg

RIG Reinforced without central pin, with single hardened and guarded ball raceway. Bolted wheel axle.



WHEEL

F - Cast Iron. Hardness: 160 Brinell. (-40°C to + 400°C)
Produced with grey cast iron, they roll easily offering a great handling effort reduction. They are very resistant withstanding high loads and temperatures. They are not indicated to utilization when noise level and floor maintenance are required.

Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GKSR 42 FR	FKSR 42 FR	R 42 FR	100	50	1/2"	Roller Bearing	500	145	75	135
GKSR 42 FE	FKSR 42 FE	R 42 FE				Ball Bearing				
GKSR 52 FR	FKSR 52 FR	R 52 FR	125			Roller Bearing	600	165	92	140
GKSR 52 FE	FKSR 52 FE	R 52 FE				Ball Bearing				
GKSR 62 FR	FKSR 62 FR	R 62 FR	150			Roller Bearing	700	190	142	180
GKSR 62 FE	FKSR 62 FE	R 62 FE				Ball Bearing				
GKSR 82 FR	FKSR 82 FR	R 82 FR	200			Roller Bearing	900	241	173	210
GKSR 82 FE	FKSR 82 FE	R 82 FE				Ball Bearing				
GKSR 102 FR	FKSR 102 FR	R 102 FR	250			Roller Bearing	900	290	211	240
GKSR 102 FE	FKSR 102 FE	R 102 FE				Ball Bearing				

Accessories/Brake Options



Side Brake - FL



Pedal Brake - FP




Swivel Lock - AD



Caster Guard - GC

Swivel Sections



Top Plate Options

