

ERGONOMIC Heavy Duty

B - MOLDED RUBBER



Load capacity up to 750kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

B - Molded Rubber. Hardness: 80 Shore A. (-20°C to + 70°C)
Produced with molded vulcanized rubber tread over a grey cast iron wheel center. They roll softly with a low noise level, absorb shocks and vibrations. They are resistant to abrasion and chemicals. They can be used at a speed of up to 20km/h when mounted with ball bearings.

Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)				
Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GKMP 63 BR	FKMP 63 BR	R 63 BR	150	70	3/4"	Roller Bearing	400	190	112	195
GKMP 63 BE	FKMP 63 BE	R 63 BE				Ball Bearing				
GKMP 83 BR	FKMP 83 BR	R 83 BR	200			Roller Bearing	500	257	155	230
GKMP 83 BE	FKMP 83 BE	R 83 BE				Ball Bearing				
GKMP 103 BE	FKMP 103 BE	R 103 BE	250			Ball Bearing	600	292	185	270
GKMP 123 BE	FKMP 123 BE	R 123 BE	300			Roller Bearing	750	343	220	310

Accessories/Brake Options



Side Brake - FL



Pedal Brake - FP




Swivel Lock - AD



Caster Guard - GC

Swivel Sections



Top Plate Options




Plate KMPA




Plate KMP