

ERGONOMIC Heavy Duty

F - CAST IRON








Load capacity up to 1200kg

RIG Reinforced rig, made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.



WHEEL

F - Cast Iron. Hardness: 160 Brinell. (-40°C to + 400°C)
Produced with grey cast iron, they roll easily offering a great handling effort reduction. They are very resistant withstanding high loads and temperatures. They are not indicated to utilization when noise level and floor maintenance are required.

Swivel Caster	Rigid Caster	Wheel	 (mm)	 (mm)	 (pol)	Axle Type (bearing)	 KG	 (mm)	 w/o brake (mm)	 w/ brake FP (mm)
Reference	Reference	Reference								
GKMP 63 FR	FKMP 63 FR	R 63 FR	150	70	3/4"	Roller Bearing	600	190	112	195
GKMP 63 FE	FKMP 63 FE	R 63 FE				Ball Bearing				
GKMP 83 FR	FKMP 83 FR	R 83 FR	200			Roller Bearing	800	257	155	230
GKMP 83 FE	FKMP 83 FE	R 83 FE				Ball Bearing				
GKMP 103 FE	FKMP 103 FE	R 103 FE	250			Ball Bearing	1000	292	185	270
GKMP 123 FE	FKMP 123 FE	R 123 FE	300			Roller Bearing	1200	343	220	310

Accessories/Brake Options



Side Brake - FL



Pedal Brake - FP



Swivel Lock - AD



Caster Guard - GC

Swivel Sections



Top Plate Options




Plate KMPA




Plate KMP