







# WHEEL NP

## POLYPROPYLENE

NP - Polypropylene Hardness: 65 Shore D. (-20°C to + 70°C)  
 Injected with recyclable polypropylene copolymer wheel center and tread. Indicated for light and medium loads, roll very easily, requiring low handling effort, resistant to deformation under static loads, with an excellent cost-benefit ratio. They present a good resistance to chemicals and moderate impacts. Nominal working speed is up to 4km/h. Produced with recycled materials.



WHEEL						Axle Type (bearing)	
Reference	(mm)	(mm)	(mm)	Axle Diameter w/ Sleeve	Axle Diameter w/o Sleeve		KG
R 158 NP	41	17	19	-	1/4"	Plain Bearing	40
R 210 NP	50	19	24				45
R 310 NP	75						60
R 410 NP	100						70
R 312 NP	75	32	38	-	5/16"	Plain Bearing	80
R 312 NPN						Plain Bearing with Thread Guards	
R 312 NPE						Ball Bearing	
R 3512 NPN	90	32	38	-	5/16"	Plain Bearing with Thread Guards	90
R 3512 NPE						Ball Bearing	115
R 412 NP	100	32	38	-	5/16"	Plain Bearing	90
R 412 NPN						Plain Bearing with Thread Guards	
R 412 NPE						Ball Bearing	
R 512 NP	125	32	38	-	5/16"	Plain Bearing	100
R 512 NPN						Plain Bearing with Thread Guards	
R 512 NPE						Ball Bearing	
R 612 NP	150	32	38	-	5/16"	Plain Bearing	125
R 612 NPE						Ball Bearing	165
R 414 NPN	100	38	48	7/16"	9/16"	Nylon Socket	125
R 414 NPE		32		-	7/16"	Ball Bearing	
R 514 NPN	125	38		7/16"	9/16"	Nylon Socket	150
R 514 NPE		32		-	7/16"	Ball Bearing	
R 614 NPN	150	38		7/16"	9/16"	Nylon Socket	165
R 614 NPE		32		-	7/16"	Ball Bearing	
R 816 NPN	200	41	54	5/8"	7/8"	Nylon Socket	200
R 816 NPE				7/8"	25mm	Ball Bearing	
R 916 NPN	225			5/8"	7/8"	Nylon Socket	220
R 916 NPE				7/8"	25mm	Ball Bearing	
R 1016 NPN	250			5/8"	7/8"	Nylon Socket	250
R 1016 NPE				7/8"	25mm	Ball Bearing	