

BALL

Load capacity up to 40kg








RIG Made of stamped steel with single ball raceway and a Chrome-Plated finish. Rivetted wheel axle.

WHEEL NP - Polypropylene Hardness: 65 Shore D. (-20°C to +70°C)
 Injected with recyclable polypropylene copolymer wheel center and tread. Indicated for light and medium loads, roll very easily, requiring low handling effort, resistant to deformation under static loads, with an excellent cost-benefit ratio. They present a good resistance to chemicals and moderate impacts. Nominal working speed is up to 4km/h. Produced with recycled materials.



Wheel Options




Swivel Caster	Swivel Caster with Brake				Axle Type (bearing)				
Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake FP (mm)
GLBP 210 NP CR	GLBP 210 NP CR SL	50	47	1/4"	Plain Bearing	40	65	47	62

Fittings/Accessories




	Top Plate	Threaded Stem 3/8" X 25mm	Threaded Stem 3/8" X 50mm	Stem Ø7/16" X 50mm	Stem Ø7/16" X 20mm	Nylon Socket Ø10 X 28mm	Nylon Socket Ø12 X 28mm	Nylon Socket Ø15 X 32mm
Reference	P	E	EX	EL	ELT	ELSH	ELSK	ELSJ

Swivel Sections



Top Plate



Brake Option



SL

NYLON SOCKET FITTING

SIZE (mm)	REFERENCE
Ø38	S1
Ø30	S2
Ø25	S3
40 x 40	S4