

COLOR GEL

Load capacity up to 60kg

RIG

Made of stamped steel with single ball raceway and a Chrome-Plated finish. Rivetted wheel axle.



WHEEL

Colorgel – Transparent Thermoplastic Polyurethane Hardness: 90 Shore A. (– 20°C to + 70°C)
Injected with a polyurethane lining and acrylic wheel center with several combinations of colors. Indicated for furniture, rolling very easily, requiring low handling effort, resistant to deformation under static loads, with an excellent cost-benefit ratio. They present a good resistance to chemicals and moderate impacts. Produced with recycled materials.



Swivel Caster	Rigid Caster	Wheel	(mm)	(mm)	(pol)	Axle Type (bearing)	KG	(mm)	w/o brake (mm)	w/ brake FPI (mm)	w/ brake FP (mm)
Reference	Reference	Reference									
MGAP 100 GEL	-	R 100 GEL	35	24	1/4"	Plain Bearing	30	48	32	-	-
MGAP 200 GEL	MFAP 200 GEL	R 200 GEL	50				40	67	43	70	53
MGAP 300 GEL	MFAP 300 GEL	R 300 GEL	75				50	92	56	84	56
MGAP 400 GEL	-	R 400 GEL	100				60	122	90	-	115

*Add desired wheel color at the end of reference.

Fittings/Accessories






	Top Plate	Threaded Stem 3/8"NC X 25mm	Threaded Stem 3/8"NC X 50mm	Stem Ø7/16" X 50mm	Nylon Socket Ø10mm X 28mm	Nylon Socket Ø12mm x 28mm	Nylon Socket Ø15mm x 32mm	Nylon Socket
Reference	AP	AE	AEX	AEL	ALSH	ALSK	ALSJ	See table below

Swivel Sections

Top Plate Options

Brake Options



NYLON SOCKET FITTING		43
SIZE (mm)	REFERENCE	
Ø38	S1	
Ø30	S2	
Ø25	S3	
40 x 40	S4	

Wheel Colors

