

# L12

## F - CAST IRON

Load capacity up to 170kg



### RIG









Made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.

### WHEEL


F - Cast Iron. Hardness: 160 Brinell. (-40°C to +400°C)

Produced with grey cast iron, they roll easily offering a great handling effort reduction. They are very resistant withstanding high loads and temperatures. They are not indicated to utilization when noise level and floor maintenance are required.




Swivel Caster	Rigid Caster	Wheel				Axle Type (bearing)					
Reference	Reference	Reference	(mm)	(mm)	(pol)		KG	(mm)	w/o brake (mm)	w/ brake G (mm)	w/ brake SL (mm)
GL 312 FN	FL 312 FN	R 312 FN	75	32	5/16"	Plain Bearing	170	103	71	98	80

### Fittings/Accessories




Reference	LES	LE	LEX	LEL	See table below	See table below	See table below	See table below
-----------	-----	----	-----	-----	-----------------	-----------------	-----------------	-----------------


### Swivel Sections






### Top Plate Options



### Brake Options



NYLON SOCKET FITTING 		RUBBER EXPANDER FITTING 		ALUMINUM EXPANDER FITTING 		CAP'S N°	THREAD
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE		
Ø38	S1	18 - 21	EX 1			T1	1/2" BSP
Ø30	S2	21 - 24	EX 2	21 - 27	EA 2	T2	3/4" BSP
Ø25	S3	25 - 28	EX 3				
40X40	S4	27 - 30	EX 4	27 - 33	EA 4	T3	1" BSP
		37 - 40	EX 5				