

L14 - S14

UP - THERMOPLASTIC POLYURETHANE

Load capacity up to 165kg

RIG

Made of stamped steel plate and swivel head with double ball raceway, zinc-plated finish. Bolted wheel axle.

WHEEL

UP - Thermoplastic Polyurethane. Hardness: 90 Shore A. (-20°C to + 70°C)
Produced with recyclable thermoplastic elastollan polyurethane tread and polypropylene copolymer wheel center. Ideal for those who look for an excellent load capacity added to great floor protection with low noise rolling, offering an excellent resistance to abrasion and impacts. Resistant to greases, mineral oils and some acids. Nominal working speed is up to 4km/h.




Swivel Caster	Rigid Caster	Swivel Caster	Rigid Caster	Wheel	(mm)	(mm)	(pol)	Axle Type (bearing)	KG	(mm)		w/o brake (mm)	w/ brake G (mm)	
Reference	Reference	Reference	Reference	Reference						GL/FL	FL/FS			
GL 414 UPN	FL 414 UPN	GS 414 UPN	FS 414 UPN	R 414 UPN	100	38	7/16"	Nylon Socket	125	135	140	88	120	
GL 414 UPE	FL 414 UPE	GS 414 UPE	FS 414 UPE	R 414 UPE		32		Ball Bearing						
GL 514 UPN	FL 514 UPN	GS 514 UPN	FS 514 UPN	R 514 UPN	125	38		Nylon Socket	150	156	161	103		
GL 514 UPE	FL 514 UPE	GS 514 UPE	FS 514 UPE	R 514 UPE		32		Ball Bearing						
GL 614 UPN	FL 614 UPN	GS 614 UPN	FS 614 UPN	R 614 UPN	150	38		Nylon Socket	165	178	183	118		130
GL 614 UPE	FL 614 UPE	GS 614 UPE	FS 614 UPE	R 614 UPE		32		Ball Bearing						

Fittings/Accessories

	Axle hole 16mm	Threaded Stem 1/2"NC X 25mm	Threaded Stem 1/2"NC X 64mm	Stem Ø7/16" X 50mm	Nylon Socket Fitting	Rubber Expander Fitting	Aluminum Expander Fitting	Fitting Cap's
Reference	LES	LE	LEX	LEL	See table below	See table below	See table below	See table below

Note: Stem casters overall heights are 3mm less than indicated on table.

Swivel Sections



Top Plate Options




Plate L




Plate S




Plate L12 Optional

Brake Option



NYLON SOCKET FITTING		RUBBER EXPANDER FITTING		ALUMINUM EXPANDER FITTING		CAP'S N°	THREAD
SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	SIZE (mm)	REFERENCE	T1	1/2" BSP
Ø38	S1	18 - 21	EX 1	21 - 27	EA 2	T2	3/4" BSP
Ø30	S2	21 - 24	EX 2				
Ø25	S3	25 - 28	EX 3	27 - 33	EA 4	T3	1" BSP
40X40	S4	27 - 30	EX 4				
		37 - 40	EX 5				